


## Datasheet

DC connector

BC03H,male,terminals crimping,non rewirable.housing color,black



Art.No.	BC03H-M-C24
Order unit	PCS

## Approvals



## Technical data

### General

Rated current	30A (TUV) , 35A (CSA)
Rated voltage	1100V DC (TUV, CSA)
Contact resistance	$\leq 0.5m\Omega$
Insulation resistance	$\geq 400M\Omega$
Rated impulse withstand voltage	6600V
Over-voltage category	III
Pollution degree	2
Waterproof Rating	IP67 (mated)
Flammability Rating	UL94-V0
IEC protection class	II
Rated temperature	-40°C~+85°C
Maximum operating temperature	115°C

### Connection Data

Number of contacts	01 Pin
Applicable wire gauge	2.5/4.0/6.0mm <sup>2</sup> or 14/12AWG
Outer cable diameter	5~6.8mm

## Model

Connector Gender	Male
Backshell Assembly Style	Straight crimp

## Material

Housing material	PC (Polycarbonate)
Contact Material	Red Copper(punching) / CuZn alloy(cutting)
Contact Surface	Tin-plated
Sealing gasket	Silicon

## Standards

EN 62852: 2014	IEC - Safety requirements and tests
UL6703	USA and Canada - Safety requirements and tests
RoHS compliant	Yes

## Dimensions

Length	56.8mm
Width	19.0mm
Height	19.0mm
Weight	7.60g

REV. 05  
2023.12.19

Wuxi Betteri Electronic Technology CO.,LTD. | Wuxi Optoelectronic Materials

Science&amp;Technology Pack 5-1,#11,Jinshan Rd.Branch#4,Wuxi,China | Tel : 0086-0510-88771606

Fax : 0086-0510-88770676 | Zip code : 214037 | Website <http://www.betteri.cn>

Your better choice